

CAT 6

- All Cables are Manufactured Under **ISO 9000 Standard**.
- ETL Verified to EIA/TIA 568A Category 6, Standard.
- UL (USA) CMR, CSA (Canada) CMG FT4, AusTel (Australia), and Fuji (Japan) Listed.
- Solid Cable with Pull cord inside and footage clearly marked on jacket.
- Packaged in 1000ft Reelbox and Tested to 500MHz.

DC-568-(CC)-1000 Stranded for Patch Cords
DC-568-(CC)-1000L Solid Horizontal Installation

Available Colors (CC) BG, BK, BL, GN, GR, OR, PK, RD, VL, WH, YW.

DC-568-(CC)-328L Solid Horizontal Installation

Available Colors (CC) BK, BL, GN, GR, OR, RD, VL, WH, YW.

DC-568-GR-1000-ZH Stranded Low Smoke Zero Halogen (LSZH) 4 Pair


1000ft.
Box




328ft.
Box



Cat.6



Solid



Stranded



Reel Box
Bulk Category Cables
Packaged in Reel Box
to Ensure the Best
Performance

ENHANCED CAT 5

- All Cables are Manufactured Under **ISO 9000 Standard**.
- ETL Verified to EIA/TIA 568A TSB-40A category 5.
- UL (USA) CMR, CSA (Canada) CMG FT4, AusTel (Australia), and Fuji (Japan) Listed.
- Solid Cable with Pull cord inside and footage clearly marked on jacket.
- Packaged in 1000ft Reelbox and Tested to 350MHz.

Solid
24 AWG

DCS-5E8(CC)-1000L CAT 5E Solid 4 Pair Conductor. 1000ft./Reel **Shielded**
CC: BL, GR, YW. **Note: Use Modular Plug PTS-03E88RG-50UL**

DC-5E8(CC)1000L CAT 5E Solid 4 Pair Conductor. 1000ft./Reel
CC: BG, BK, BL, GN, GR, LG, OR, PB, PK, RD, VL, YW, WH

DC-5E8(CC)328L CAT 5E Solid 4 Pair Conductor. 328ft. (100M). Mini Box
CC: BK, BL, GN, GR, OR, PB, PK, RD, VL, YW, WH.

DC-5E4(CC)1000-L CAT 5 Solid 2 Pair Conductor, Gray Jacket
CC: BL, GR.



1000ft.
Box

5E

328ft.
Box



DC-5E8(CC)1000L

DC-5E8(CC)328L

Solid
Economic

DC-5E8-(CC)-1KL CAT 5E Solid 4 Pair Conductor. 1000ft./Pull Box. **CC:** BL, GN, GR, RD, YW, WH.

Stranded
26 AWG

DCS-5E8-(CC)1000 CAT 5E Stranded 4 Pair Conductor, 1000ft./ Reel **Shielded**
CC: BK, BL, GN, GR, OR, RD, VL, YW, WH.

DC-5E4(CC)2000 CAT 5E Stranded 2 Pair Conductor, 2000ft./ Reel
CC: BK, BL, GR, WH.

DCS-5E6GR1000 CAT 5E Stranded 3 Pair Conductor, 1000ft./ Reel, Gray Cable

DC-5E8(CC)1000 CAT 5E Stranded 4 Pair Conductor. 1000ft./ Reel
CC: BG, BK, BL, GN, GR, LG, OR, PB, PK, RD, TC, TL, VL, YW, WH

DC-5E8(CC)1000-ZH CAT 5E Stranded LSZH, 4 Pair Conductor, 1000ft./ Reel
CC: BL, GR, OR, RD, WH

NEW
Color



CAT 5

- All Cables are Manufactured Under **ISO 9000 Standard** and are UL and CSA listed.
- ETL Verified to EIA/TIA 568A Category 5. CMR, PVC jacket.
- Solid Cable with Pull cord inside and footage clearly marked on jacket.
- Packaged in 1000ft Reelbox

DC-554(CC)1000

Stranded 2 Pair **CC:** BG, BK, BL

DC-558WH1000-LT

Teflon CAT 5 Solid 4 Pair White Jacket



CAT
5

(CC) Color Abbreviation Chart	Beige (BG)	Black (BK)	Blue (BL)	Green (GN)	Gray (GR)	Ivory (IV)	Lime Green (LG)	Orange (OR)	Powder Blue (PB)	Pink (PK)	Red (RD)	Translucent Clear (TC)	Teal (TL)	Violet (VL)	Yellow (YW)	White (WH)
-------------------------------------	---------------	---------------	--------------	---------------	--------------	---------------	-----------------------	----------------	------------------------	--------------	-------------	------------------------------	--------------	----------------	----------------	---------------

FLAT CABLE

- 26 AWG Silver Satin (SV) or Black (BK)
- Unshielded Cable

<u>DC-W4-500BK</u>	<u>DC-W4-100</u>
<u>DC-W6-500BK</u>	<u>DC-W6-100</u>
<u>DC-W8-500BK</u>	<u>DC-W8-100</u>
<u>DC-W4-1000BK</u>	<u>DC-W4-500</u>
<u>DC-W6-1000BK</u>	<u>DC-W6-500</u>
<u>DC-W8-1000BK</u>	<u>DC-W8-500</u>
<u>DC-W4-50</u>	<u>DC-W10-500</u>
<u>DC-W6-50</u>	<u>DC-W4-1000</u>
<u>DC-W8-50</u>	<u>DC-W6-1000</u>
<u>DC-W4-75</u>	<u>DC-W8-1000</u>
	<u>DC-W10-1000</u>

- 26 AWG Silver Satin (SV)
- Unshielded Cable

<u>DC-W4-500UL</u>
<u>DC-W4-1000UL</u>
<u>DC-W6-500UL</u>
<u>DC-W6-1000UL</u>
<u>DC-W8-500UL</u>
<u>DC-W8-1000UL</u>




- 26 AWG Ivory (IV) or White (WH)
- Unshielded Cable

<u>DC-W4-1000IV-UL</u>
<u>DC-W4-1000WH-UL</u>
<u>DC-W6-1000WH-UL</u>

Econo Type

- 28 AWG Silver
- TELE WIRE, 1000ft Roll

DC-W8-1K



DC-W8-100

TWISTED PAIR CABLE

- Unshielded Twisted Pair Cables
- Silver Satin (SV) or Black (BK) Stranded

<u>DC-WT6-(LL)-SV-24UL</u>
<u>DC-WT8-(LL)-SV-24UL</u>



24 AWG Silver

<u>DC-WT6-(LL)-SV-24</u>

24AWG Gray, 4 Conductor Solid


<u>DC-WST4-100024GR</u>

26 AWG Silver

<u>DC-WT2-1000</u>
<u>DC-WT4-1000</u>
<u>DC-WT6-(LL)</u>
<u>DC-WT8-(LL)</u>
<u>DC-WT10-(LL)</u>



DC-WT4-1000



24 AWG Black

<u>DC-WT4-(LL)-BK-24</u>
<u>DC-WT6-(LL)-BK-24</u>

<u>DC-WT4-(LL)-BK-24UL</u>
<u>DC-WT6-(LL)-BK-24UL</u>
<u>DC-WT8-(LL)-BK-24UL</u>

Available Footage (LL): 500, 1000 Roll.

BNC COLOR CODED BOOTS

- For RG-58A & 59 Strain Relief.

<u>BTS-58-(CC)</u>
<u>BTS-59-(CC)</u>



CC: BK, BL, GN, GR, RD, WH, YW.

SHIELDED CAT 5E



All cables are made to **ISO 9000 Standard** (European Shielded Standard). Stranded with 26 AWG twisted pair conductors. Solid with 24 AWG twisted pair conductors. Verified to EIA/TIA 568B.2 category 5e. Package in 1000ft Reelbox.

DCS-5E8(CC)1000L Solid

CC: BL, GR, YW.

Note: Use Modular Plug PTS-03E88RG-50UL

DCS-5E8(CC)1000 Stranded

CC: BK, BL, GN, GR, OR, RD, VL, WH, YW.



BULK COAX CABLE

- RG-58, 500 ft roll

RG-58AU-500 Stranded Center Conductor

RG-58U-500 Solid Center Conductor



COAX PLUG COLOR BAND

- For BNC and TNC Only.

CCB-(CC)



CC: BK, BL, GN, OR, RD, WH, YW.

(CC) Color Abbreviation Chart	Beige (BG)	Black (BK)	Blue (BL)	Green (GN)	Gray (GR)	Ivory (IV)	Lime Green (LG)	Orange (OR)	Powder Blue (PB)	Pink (PK)	Red (RD)	Translucent Clear (TC)	Teal (TL)	Violet (VL)	Yellow (YW)	White (WH)
-------------------------------------	---------------	---------------	--------------	---------------	--------------	---------------	-----------------------	----------------	------------------------	--------------	-------------	------------------------------	--------------	----------------	----------------	---------------