



## SPECIFICATIONS

- Input voltage:	See chart
- Output voltage:	See chart
- Output current:	500 mA
- Frequency:	50-60 Hz
- Ripple+Noise:	15 mV @ 0.5 A
- Temperature rating:	0°...+50°C
- Load regulation:	100 mV
- Electrical protections:	Overload and overvoltage
- Enclosure protection:	IP 20 according to EN 60529
- Connections:	Screw connectors
- Electromagnetic compatibility	EN 55011 class B / EN 50082-2 / EN 61000-3-2
- Mounting:	DIN rail mounting



## FEATURES

The GSA LCC is covered with a plastic guard of only 22.5 mm in width and it is suitable for DIN rail mounting. This AC/DC stabilization unit is provided with a built-in fixed low tension regulator and can supply the maximum power of 12W. Available with different working voltages.

## HOW TO ORDER

Model	Code	V <sub>IN</sub> AC [V]	V <sub>OUT</sub> DC [V]	I <sub>OUT</sub> [A]	Dimensions [mm]			Weight [Kg]
					L	h	p	
GSA LCC5	001590	8±10%	5	0.5	22.5	75	87	0.1
GSA LCC12	001593	12±10%	12	0.5	22.5	75	87	0.1
GSA LCC15	001594	15±10%	15	0.5	22.5	75	87	0.1
GSA LCC18	001595	18±10%	18	0.5	22.5	75	87	0.1
GSA LCC24	001597	24±10%	24	0.5	22.5	75	87	0.1

## DIMENSIONS

