

## SPECIFICATIONS

- Input voltage:	See chart
- Output voltage:	See chart
- Output current:	500 mA
- Frequency:	50-60 Hz
- Ripple+Noise:	15 mV @ 0.5 A
- Temperature rating:	0°...+50°C
- Load regulation:	100 mV
- Electrical protections:	Overload and overvoltage
- Enclosure protection:	IP 20 according to EN 60529
- Connections:	Screw connectors
- Electromagnetic compatibility	EN 55011 class B / EN 50082-2 / EN 61000-3-2
- Mounting:	DIN rail mounting



## FEATURES

This AC/DC stabilization unit is provided with a built-in fixed low tension regulator and can supply the maximum current of 1,5A. Is prepared for DIN rail mounting and is supplied with a protection cover against accidental contacts.

## HOW TO ORDER

Model	Code	V <sub>IN</sub> AC [V]	V <sub>OUT</sub> DC [V]	I <sub>OUT</sub> [A]	Dimensions [mm]			Weight [Kg]
					L	h	p	
GSA LCF5	001690	8±10%	5	1.5	68.5	66	80	0.145
GSA LCF6	001691	8±10%	6	1.5	68.5	66	80	0.145
GSA LCF8	001692	8±10%	8	1.5	68.5	66	80	0.145
GSA LCF12	001693	12±10%	12	1.5	68.5	66	80	0.145
GSA LCF15	001694	15±10%	15	1.5	68.5	66	80	0.145
GSA LCF18	001695	18±10%	18	1.5	68.5	66	80	0.145
GSA LCF20	001696	20±10%	20	1.5	68.5	66	80	0.145
GSA LCF24	001697	24±10%	24	1.5	68.5	66	80	0.145

## DIMENSIONS

