

SPECIFICATIONS

- Input voltage:	100-240 V AC (autoswitch)
- Output voltage:	See chart
- Output nominal current:	See chart
- Frequency:	47-63 Hz
- Ripple+Noise:	<150 mV @ 100% of load
- Temperature rating:	0°...+50°C
- Cooling:	Convention cooled
- Electrical protection:	Short circuit (autorecovery) and overload protection (Automatic power limited)
- Enclosure protection:	IP 20 according to EN 60529
- Efficiency:	80% minimum (@ 24 V DC)
- Connection:	Screw connectors
- Safety:	EN 60950
- Electromagnetic compatibility (EMC):	EN 55011 class B / EN 50082-2 / EN 61000-3-2
- Mounting:	DIN rail mounting



FEATURES

The series GSA SWLC 04 is a "low cost" version of single phase switching power supply. It is characterized by 100-240 V AC input voltage. The output voltage is adjustable for all the models ($\pm 10\%$).

HOW TO ORDER

Model	Code	V _{IN} AC [V]	V _{OUT} DC [V]	I _{OUT-NOM.} [A]	Dimensions [mm]			Weight [Kg]
					L	h	p	
GSA SWLC04/5	002204	100÷240	5±10%	20	35	99	199	0.6
GSA SWLC04/12	002205	100÷240	12±10%	8.3	35	99	199	0.6
GSA SWLC04/15	002211	100÷240	15±10%	6.7	35	99	199	0.6
GSA SWLC04/24	002206	100÷240	24±10%	4.5	35	99	199	0.6

DIMENSIONS

