

**DVA30**

**Non-Contact AC Voltage and Current Detector**

**\$39**

Detects and pinpoints wide range Voltage and Current with Sensitivity adjust



Locates current flow even where voltage detectors cannot work.

**Features:**

- The only two-in-one current/voltage detector designed for electrical testing
- Non-Contact AC Voltage detection from 12V to 600VAC
- Non-Contact AC Current detection from 200mA to 1000A
- Sensitivity adjustments to increase or reduce sensor trigger threshold
- Loud audible and bright visible current and voltage detect indicators
- Convenient pocket size with clip
- Current sensor detects current flow through shielded wires, conduit, and metal circuit breaker/junction boxes
- Current function detects current flow of 400mA at 0.2" (5mm) distance and at much greater distances for larger current flows
- UL and CE approved; CAT III-600V
- 1 year warranty
- Dimensions/Wt: 7.6x1.2x0.9" (192x31x24mm) / 2.1oz (60g)
- Complete with four LR44 button batteries and pocket clip

**Applications**

- Trace concealed wires in walls and floors
- Identify "hot" wires
- Trace current flow behind walls, in conduit, where voltage detection does not work
- Sensitivity high enough to trip on low voltage HVAC or similar signal levels

**Ordering**

DVA30 .....Non-Contact AC Voltage and Current Detector .....\$39  
CA895 .....Vinyl pouch carrying case with belt strap.....\$10

**DA30**

**Non-Contact Current Detector**

**\$29**

Locates current in hidden wires and cables



Non-contact AC Current measurements from 200mA to 1000A

**Features:**

- Non-contact AC Current range is from 200mA to 1000A
- Locates current flow even where voltage detectors cannot work
- Detects through shielded wires, conduit, and metal circuit breaker or junction boxes
- Sensitivity adjustment for locating wires/conduit through walls
- Audible and visible indication
- UL and CE approved; CAT III-600V
- 1 year warranty
- Dimensions: 5.7x1.1x1" (145x28x25mm); Weight: 1.6oz (45g)
- Complete with pocket clip and four LR44 button batteries

**Ordering**

DA30 .....Non-Contact Adjustable AC Current Detector .....\$29  
CA895 .....Vinyl pouch carrying case with belt strap.....\$10

DV30

## Adjustable AC Voltage Detector

**NEW!**

\$13

Sensitivity adjust to pinpoint Voltage source

### Features:

- Non-Contact detection of AC Voltage from 12VAC to 600VAC
- Sensitivity adjustment increases or reduces sensor trigger threshold
- Audible and visible voltage indication
- Self test function
- UL and CE approved; CAT III-600V
- 1 year warranty
- Dimensions: 6.1x1.1x1" (155x28x25mm); Weight: 1.5oz (42g)
- Complete with pocket clip and four LR44 button batteries



### Ordering

DV30	Non-Contact Adjustable AC Voltage Detector	\$13
CA895	Vinyl pouch carrying case with belt strap	\$10

40130

## AC Voltage Detector

\$10

Non-contact detection of AC Voltage

### Features:

- Non-Contact Detection of AC Voltage from 100VAC to 600VAC
- For use on 50/60Hz circuits
- Tip fits into outlets or against wire insulation
- Flashing red LED light and push button ON/OFF Audible beeper indicator
- Locate breaks in power cables
- UL and CE approved; CAT III-600V
- Lifetime warranty
- Dimensions: 6x0.75x1" (152x19x25mm)  
Weight: 2oz (57g); includes pocket clip
- Complete with pocket clip and two AAA batteries



### Ordering

40130	Non-Contact AC Voltage Detector	\$10
CA895	Vinyl pouch carrying case with belt strap	\$10

ET34

## Voltage and Continuity Tester

\$39

LED indication of AC/DC Voltage to 480V in seven ranges

### Features:

- Bright indicating LEDs at 12, 24, 120, 208, 240, 277 and 480V
- Audible and Visible continuity test up to 200kΩ
- Single pole live voltage detector
- Voltage function operates without batteries
- Automatic AC/DC indication plus DC polarity
- CAT III-600V
- Dimensions: 8.3x1.6x0.9" (210x40x22mm)  
Weight: 4.6oz (130g)
- Complete with 39" (1m) cable with test lead and two 1.5V AAA batteries



### Ordering

ET34	Voltage and Continuity Tester	\$39
------	-------------------------------	------