



401014
\$25

Big Digit Indoor/Outdoor Thermometer

Built-in memory stores Minimum and Maximum Temperature readings

- Large LCD displays 1" (25mm) digits for indoor/outdoor temperature
- Indoor Range: 14 to 140°F (-10 to 60°C)
Outdoor Range: -58 to 158°F (-50 to 70°C)
±1.8°F/1°C accuracy; 0.1°F/°C resolution
Dims: 4.4x4x0.9" (112x102x22mm)
Weight: 6.5oz (186g)
- Complete with weatherproof temperature sensor with 9.6ft (3m) thin cable, stand, AAA battery, and wall mounting bracket



TE414
\$29

Wireless (433MHz) Temperature System

Local and remote monitoring of up to 3 transmitters with one base station

- Displays local/remote Temperature & time
- Transmitters wall mount up to 82ft (25m)
- Base: 32 to 140°F (0 to 60°C)
Transmitter: -22 to 158°F (-30 to 70°C)
±1.8°F (0.8°C) accuracy; 0.1°F/°C res.
Dims: Base-2.4x1.2x6.2" (60x31x157mm)
Transmitter-1.6x0.9x5" (40x23x128mm)
Weight: Base-9oz (257g) Trans.-3oz (86g)
- Complete with one base station, stand, 2 AA batteries, one TE415 transmitter, mounting bracket and 2 AAA batteries. Additional Transmitters sold separately.



39240
\$19

Waterproof Thermometer

Pocket size with Max/Min recording

- 2.75" (70mm) Stainless steel stem
- Data Hold and Auto power off
- Temperature: -40 to 392°F (-40 to 200°C), ±2°F/1°C accuracy, 0.1°/1° resolution
Dims: 5.9x0.8x0.7" (150x20x18mm)
Weight: 0.7oz (20g)
- Complete with one LR44 button battery and protective cover



392052
\$25

Flat Surface Stem Dial Thermometer

Measures temperature on surfaces such as grills and motors

- 5" (130mm) stainless steel probe with 2" (54mm) dial
- ON/OFF switch saves battery life
- Auto Power off after 1 hour
- Temperature: -58 to 572°F (-50 to 300°C), ±2°F/1°C accuracy; 0.1°/1° resolution
Weight: 1oz (29g)
- Complete with 1.5V LR44 button battery



39272
\$39

Pocket Fold-up Thermometer with Adjustable probe

4.5" (114mm) stainless steel probe adjusts from 0 to 180° for storage or measurement

- Detents at 45°, 90°, 135°, and 180°
- Fast response; Auto Power off after 1hour
- Data Hold and Min/Max
- Temperature: -58 to 572°F (-50 to 300°C), ±1.8°F/1°C, 0.1°/1° resolution
Dims: 6.1x2x0.8" (154x50x20mm)
Weight: 2.5oz (71g)
- Complete with wrist strap & AAA battery



392085
\$29

Pocket Thermometer with Alarm

Audible High/Low Alarms

- Audible alarm alerts user when pre-set max or min temperature is reached or exceeded
- Data Hold
- Durable 2.5" (64mm) stainless steel probe with 20" (508mm) cable
- Temperature: -58 to 302°F (-50 to 150°C), ±1.8°F/1°C accuracy, 0.1°/1° resolution
Dims: 4.8x3x0.8" (122x76x20mm)
Weight: 3.4oz (96g)
- Complete with wallet style case, stainless steel probe, and 1.5V button battery

All Hygro-Thermometers featured on pages 68-69 are CE Certified and include 1 year warranty. * Model 44539 is not CE approved



HW30

\$29

Stopwatch display

HeatWatch™

Digital Stopwatch includes Temperature, Humidity, and Heat Index

- Temperature, Humidity, and Heat Index display mode
- Alarm sounds when programmable Heat Index limit is exceeded
- Accumulated elapsed/split time
- 12 or 24hr clock operation
- Complete with 39" (1m) lanyard and one CR2032 battery (see p. 114 for more details)



445702

\$29

Hygro-Thermometer Clock

Combines three displays for Time, Temperature, and Humidity

- Clock displays 12/24 hour time
- Max/Min with "reset" function
- Humidity: 10 to 85% RH
Temp: 14 to 140°F or -10 to 60°C
Accuracy: ±6%RH; ±1.8°F, ±1°C
- Dims: 4.3x2.8x0.8" (109x71x20mm)
Weight: 4oz (113g)
- Complete with stand, wall mounting bracket, and 1.5V AAA battery



445703

\$39

Big Digit Hygro-Thermometer

1" Digits on Super Large LCD

- Max/Min with "reset" function
- Humidity: 10 to 99% RH
Temp: 14 to 140°F or -10 to 60°C
Accuracy: ±5%RH; ±1.8°F, ±1°C
- Dims: 4.3x3.9x0.78" (109x99x20mm)
Weight: 6oz (169g)
- Complete with stand, wall mounting bracket, and 1.5V AAA battery



44550

\$29

Pocket Humidity/ Temperature Pen

Built-in sensors provide simultaneous readings of Relative Humidity and Temperature

- Humidity: 20 to 90%RH (±5%RH)
Temp: 14 to 122°F or -10 to 50°C
Accuracy: ±5%RH; ±2°F, ±1°C
- Max/Min with "Clear" function
- Dims: 5.9x0.8x0.7" (150x20x18mm)
Weight: 0.7oz (20g)
- Complete with pocket clip and one LR44 button battery



TH433

\$79

Wireless Hygro-Thermometer System

Monitors local plus up to six remote locations from one base station (433MHz)

- Base station's LCD displays Time (alarm), Temperature, % RH; updates every minute
- Mount Remote Transmitter max 90' (28m)
- Humidity: 20 to 90%RH
Base Temp: 32 to 122°F or 0 to 50°C
Transmitter: -13 to 140°F or -25 to 60°C
Accuracy: ±5%RH; ±1.8°F, ±1°C
- Dims: Base- 4.5x5.7x1.2" (115x145x30mm)
Transmitter- 4.3x2.4x1.2" (110x60x30mm)
Wt: Base- 7.1oz (200g) Trans.- 3.2oz (90g)
- System complete with one base station, 3 AA batteries, 117VAC adaptor plus one transmitter with 2 AAA batteries. Additional (TH437)transmitters sold separately.



44539*

\$49

Executive Desktop Clock

Executive style desktop clock includes Temperature and Humidity indicators

- Elegant brushed matte aluminum face with glass lens and weighted base
- 7.5" (195mm) diameter face with second hand
- Relative Humidity dial displays 10 to 90%RH with 3%RH basic accuracy
- Thermometer dial displays -30 to 110°F (-30 to 40°C) with 3.6°F (2°C) basic accuracy
- Weight: 2lb (907g)
- Complete with 1.6V AA battery

Accessories

TH437 ...RH/Temp Transmitter for TH433...\$29