

## RIGHT ANGLE IEC STANDARD AC MALE PLUG

A three prong male power cord connector. Mates with Philmore No. 8522. Accepts cords up to .315" O.D.. Rated at 10A @ 250 VAC, and is UL Listed.

**No. 8922** - Right Angle Male  
10 @ 250 VAC, UL



## RIGHT ANGLE IEC STANDARD AC FEMALE RECEPTACLE

A three prong female power cord receptacle. Mates with Philmore No. 8525, No. 8527 and No. 8529. Accepts cords up to .315" O.D.. Rated at 10A @ 250 VAC, and is UL Listed.

**No. 8923** - Right Angle Female  
10 @ 250 VAC, UL



## MINI EXTENSION CORD

A foot long of SJT16/3 cord with 3 prong plug on one end and receptacle on the other. Use with wall outlets or power strip. Use with AC wall transformer & Power supplies to prevent blocking adjacent sockets.



**No. 48-123**



## CIGARETTE LIGHTER SOCKET PROTECTIVE DUST COVER

Fits any standard panel mount cigarette lighter socket. Made of black flexible Nylon. Safety protection for lighter socket when not in use.



**No. 48-610**



## SAFTY DUAL ADAPTOR CIGARETTE LIGHTER SOCKET

Converts a single cigarette lighter socket into a dual input. Fused lighter plug (2 amp fuse) with two side spring contacts to two lighter sockets with safety dust cover and LED indicator light on both sockets. Cable length is 10".



**No. 48-660**

## DC PLUGS EXTENSION CABLE:

A six foot cable (20 AWG) with two pin sockets molded on each end. used with Philmore interchangeable DC plugs (48- series).

**No. 48-1202**



## INTERCHANGEABLE DC PLUGS

<p>2.5mm Male</p> <p>No. 48-2500</p>	<p>3.5mm Male</p> <p>No. 48-3500</p>	<p>9V Battery Snap</p> <p>No. 48-9000</p>	<p>2.1 x 5.0mm</p> <p>No. 48-2150</p>	<p>2.1 x 5.5mm</p> <p>No. 48-2155</p>	<p>2.5 x 5.5mm</p> <p>No. 48-2555</p>
<p>1.5 x 5.5 mm</p> <p>No. 48-1555</p>	<p>1.7 x 4.0mm</p> <p>No. 48-4740</p>	<p>1.75 x 4.75mm</p> <p>No. 48-1475</p>	<p>1.35 x 3.5mm</p> <p>No. 48-3535</p>	<p>1.0 x 3.0mm</p> <p>No. 48-1030</p>	<p>0.75 x 2.35mm</p> <p>No. 48-475</p>
<p>2.5 x 5.0mm</p> <p>No. 48-2550</p>	<p>1.5 x 5.0mm</p> <p>No. 48-1550</p>	<p>2.8 x 5.5mm</p> <p>No. 48-5528</p>	<p>3.0 x 6.3mm</p> <p>No. 48-6330</p>	<p>1.0 x 7.0mm</p> <p>No. 48-480</p>	