

USB 2.0 Cables*

These cables are to be used with USB devices. They are four conductor cables with two different size of connectors. USB "A" connector is a rectangular connector and somewhat larger than the USB "B" connector which is more square in design. Both are available in male and female versions. The "A" connector is usually used where the connection is to be more permanently connected where as the "B" connector is used where the peripheral may be plugged and unplugged frequently.

USB "A" / "A" Cables

- No. 70-8113 "A" / "A" 3'
- No. 70-8116 "A" / "A" 6'
- No. 70-8115 "A" / "A" 15'

USB "B" / "B" Cables

- No. 70-8223 "B" / "B" 3'
- No. 70-8226 "B" / "B" 6'
- No. 70-8235 "B" / "B" 15'

USB "A" / "B" Cables

- No. 70-8123 "A" / "B" 3'
- No. 70-8126 "A" / "B" 6'
- No. 70-8135 "A" / "B" 15'

*USB 2.0 CABLES ARE BACKWARD COMPATIBLE TO VERSION 1.1

UPGRADE



USB Dual Port Adaptor

With this dual receptacle bracket you can update your computer to enable the use of USB peripherals. You must have Windows '95 Rev. B or later. The device is equipped with two (2) USB "A" Female receptacles with leads which can be plugged onto the computers motherboard



No. 70-8405

USB 2.0 MINI HUB

The HUB makes connections of a series of USB devices "Downstream" (away from the computer or controlling device) much easier. There is one (1) USB "B" receptacle Upstream (to connect toward the computer or controller) and four (4) USB "A" receptacles for down stream devices. With the use of this HUB you can connect more USB peripherals without needing more ports on the computer. The tiered star topology supports up to 6 tiers and 127 USB devices. Compatible with Windows 98, ME, 2000, XP and Macintosh 8.6 and later.

Features

- USB 2.04 Revision 1.1 Compliant
- Tiered Topology
- Supports up to 127 Devices
- LED Activity lights
- Power LED Light
- Support full speed 12Mbps & 480Mbps
- Low-speed 1.5Mbps
- Complete with power Supply

UPGRADE



No. 70-8804

USB PCI Controller Card

This is a complete controller Card for USB devices. It is designed to be plugged into the PCI slot on your motherboard. This allows you to upgrade your computer and provides you with two (2) USB ports. You can use any USB device such as keyboards, mice, scanners, and digital cameras.

Features

- Universal Serial Bus Interface
- Dual USB Port
- Intel UHCI (Universal Host Controller Interface)
- Normal & Low Power Operating Mode
- PCI Interface
- Fully Plug & Play Compatible
- Both MAC & PC Compatible



No. 70-8402

USB Adaptors

These adaptors allow the user to change the style, gender or couple a cable or cables together to fit their needs. These adaptors are ALL passive devices.



No. 70-8001

USB "A" Female to "B" Male



No. 70-8002

USB "A" Male to "B" Female



No. 70-8003

USB "A" Female to "B" Female



No. 70-8004

USB "A" Male to "A" Male



No. 70-8005

USB "A" Female to "A" Female



No. 70-8006

USB "B" Male to "B" Male



No. 70-8007

USB "B" Female to "B" Female

USB Video Adaptor

This USB Video adaptor is the ideal video capture device. It has both S-Video connector and RCA connector and is a bridge between PC and analog cameras, VCR's and Camcorders. It captures both still and full motion video.

Features

- Video Input 1 RCA , 1 S-Video
- Snap shot mode: 640 X 480 pixels
- 30fps @ CIF size (352 X 288 pixels)
- Converts analog Video to AVI file
- USB 1.0 Compliant
- Supports both NTSC & PAL systems
- Supports both MAC & PC formats



No. 70-8807

COMPUTER - USB CABLES & ADAPTORS

USB to USB Link Adaptor

This device provides an economical solution for a small business / home office two (2) station network. It allows Windows'95 Rev. B or Windows 98 or later PC with a USB Port to connect directly to a similarly equipped PC. Provides same resource sharing like a 10Base-T Ethernet network.

Includes
Instruction Manual
Required Software
USB Device Cable



No. 70-8808

USB to USB SmartNet Cable

This is a USB to USB network bridge. The device provides a quick and easy solution to construct a network environment, share resources such as files, printers, and storage devices. It is very useful for SOHO users, mobile users, and network gamers. Software included

Features
Supports USB network up to 17 PC's
Share resources such as Printers, scanners, modems, CD-Roms, etc.
Supports TCP/IP, NetBEUI, IPX/SPX Protocols
Suitable for SOHO & Mobile Network



No. 70-8806

USB Ethernet Adaptor

The USB Ethernet adaptor performs USB "HOT" Plug & Play operations to the Ethernet network. There is no need to open your computer to connect to the network. The unit requires a CAT5 or higher cable (not included) for Ethernet operation. Maximum cable length between the adaptor and supporting Ethernet HUB is 300' and requires a RJ45 plug on each end of a cable wired straight through.

Features
Advanced 16 bit Processor for USB transaction and control data processing
USB interface version 1.1 compliant
USB BUS I/O base address, along with interrupt number, assigned by Plug & Play system.
Upstream Port is USB "B" receptacle
Downstream Port RJ45 Jack

Includes
USB Ethernet adaptor
USB "A" / "B" Cable 6'
USB Ethernet driver CD
User's Manual



No. 70-8800

USB to Parallel Cable

USB Parallel Cable allows PC's with a USB port to print to any parallel printer. It provides truly Bi-directional, USB Plug & Play capability. Just plug the USB "A" connector into the computers USB Port and the other end into a IEEE1284 Printer using a CEN36 connector. It is fully compatible with Windows 95/ Rev. B, Windows 98 or higher.



No. 70-8010 USB "A" / CEN36 (M) 10'

USB Repeater Cable

USB Repeater cable allows the cable length on a USB device to be extended up to an additional 80 feet. You can connect up to (5) 16 foot cables serially. This is an active cable with USB "A" connector on each end that acts as a transparent buffered HUB.

Features
Compatible with MAC & IBM PC's
Compatible with Windows 95 Rev 2.1, or higher



No. 70-8125 USB "A" (M) / (F) 8'
No. 70-8150 USB "A" (M) / (F) 16'

USB to PS/2 Active Adaptor

This Active USB Adaptor makes it possible for PS/2 I/O devices such as keyboards and mice to enjoy USB Plug & Play features. Both the mouse and keyboard may be plugged in at the same time.

Features
Cable length 2.5'
(1) USB "A" Connector
(2) Downstream PS/2 Connectors
Supports Microsoft IntelliMouse
Sleep mode Power Management



No. 70-8803 USB "A" (M) / (2) MD6 (F) 2.5'

USB Serial Converter

This USB serial converter is ideal for cellular telephones, digital cameras, modems, and PDA's providing the advantages of USB Plug & Play and faster data transfer.

Features
Host Drivers Included
Advanced 16 bit processor for USB & Control Data Processing
Compatible with USB 1.1 Specifications
Upstream port USB "B" Female
Downstream port DB25 Male



No. 70-8802 USB "B" (F) / DB25 (M)