


General Purpose — Type 3TC

 <p>3TC44</p> <p>3TC52</p>	Ordering Information <ul style="list-style-type: none"> ▶ Select Contactor from table below. ▶ To complete catalog number replace the two daggers (††) with appropriate coil voltage suffix. See corresponding coil voltage suffix table. ▶ Technical Data see page 469. ▶ Dimensions see page 472. ▶ Replacement Parts see page 882. ▶ Surge Suppressors page 412. 	Coil Suffix Table																																						
		<table border="1"> <thead> <tr> <th>AC V 50/60 Hz</th> <th>Code</th> <th>DC V</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>24</td><td>C2</td><td>24</td><td>B4</td></tr> <tr><td>120</td><td>K2</td><td>36</td><td>V4</td></tr> <tr><td>240</td><td>P2</td><td>48</td><td>W4</td></tr> <tr><td>460</td><td>V0</td><td>60</td><td>E4</td></tr> <tr><td>600</td><td>S0</td><td>110</td><td>F4</td></tr> <tr><td></td><td></td><td>125</td><td>G4</td></tr> <tr><td></td><td></td><td>180</td><td>K4</td></tr> <tr><td></td><td></td><td>230</td><td>P4</td></tr> </tbody> </table>	AC V 50/60 Hz	Code	DC V	Code	24	C2	24	B4	120	K2	36	V4	240	P2	48	W4	460	V0	60	E4	600	S0	110	F4			125	G4			180	K4			230	P4	Replace †† in the contactor catalog number with a coil code from the table above.	
AC V 50/60 Hz	Code	DC V	Code																																					
24	C2	24	B4																																					
120	K2	36	V4																																					
240	P2	48	W4																																					
460	V0	60	E4																																					
600	S0	110	F4																																					
		125	G4																																					
		180	K4																																					
		230	P4																																					

DC Operated

Size	Ampere Rating		DC HP Ratings					Auxiliary Contacts Type		Catalog No	Price \$
	Open	Enclosed	115V	230V	500V	575V	750V	NO	NC		
2	32	29	3	5	10	10	5	2	2	3TC4417-0A††	501.
4	75	68	7½	15	40	40	60	2	2	3TC4817-0A††	847.
8	220	200	25	50	100	100	125	2	2	3TC5217-0A††	1348.
12	330	300	40	75	150	150	300	2	2	3TC5617-0A††	4237.

AC Operated

Size	Ampere Rating		DC HP Ratings					Auxiliary Contacts Type		Catalog No	Price \$
	Open	Enclosed	115V	230V	500V	575V	750V	NO	NC		
2	32	29	3	5	10	10	5	2	2	3TC4417-0B††	375.
4	75	68	7½	15	40	40	60	2	2	3TC4817-0B††	674.
8	220	200	25	50	100	100	125	2	2	3TC5217-0B††	1136.
12	330	300	40	75	150	150	300	2	2	3TC5617-0B††	3274.