








Type 8WA1 Ground, Neutral Isolating Terminals

Illustration	Approval	UL	CS	IEC	Description	Assembly Width	Catalog No	Price Each \$	Std Pack Qty
--------------	----------	----	----	-----	-------------	----------------	------------	---------------	--------------

Ground Terminals with 1 Screw Terminal or 2 Screw Terminals and Connection to Standard Mounting Rail, with Green/Yellow Thermoplastic Body

 <p>Terminal Size 16 2.08 (53) 1.61 (41) 1.53 (39)</p>	Maximum Current	Grounding	Grounding	Grounding	2 screw terminals	0.47 (12)	8WA1011-1PK00	5.80	50
	Wire Range	#12-#4 AWG [Ⓞ]	—	Solid 2.5 mm ² -16 mm ² Finely Stranded 10 mm ² -16 mm ²					
	Voltage Rating	—	—	—					
	Wire Strip Length	0.67 (17)							
	Recommended Screw Tightening Torque	10.6 lb-in. (1.2 Nm)							
	Density	25 pcs/ft (83 pcs/m)							
 <p>Terminal Size 35 2.08 (53) 1.96 (50)</p>	Maximum Current	Grounding	Grounding	Grounding	2 screw terminals	0.63 (16)	8WA1011-1PM00	9.70	50
	Wire Range	#10-#1 AWG [Ⓞ]	—	Solid 4 mm ² -50mm ² Finely Stranded 10 mm ² -35 mm ²					
	Voltage Rating	—	—	—					
	Wire Strip Length	0.67 (17)							
	Recommended Screw Tightening Torque	26.5 lb-in. (3 Nm)							
	Density	19 pcs/ft (62 pcs/m)							
 <p>Terminal Size 95 75 1.96 (50)</p>	Maximum Current	Grounding	Grounding	Grounding	2 screw terminals	1.02 (26)	8WA1011-1PQ00	49.00	10
	Wire Range	AWG	1/0 AWG 250mm	Finely Stranded 35mm ² - 95mm ²	Accessories				
	Voltage Rating	—	—	—	Marking tag		8WA807	1.80	100
	Wire Strip Length	0.43 (11)							
	Recommended Screw Tightening Torque	88.3 lb-in (10 Nm)							
	Density	11 pcs/ft (38 pcs/m)							

Neutral Isolating Terminal for Use in International Application, Provides for Mounting and Connection to 6 mm x 6 mm Neutral Bus Bar

 <p>Terminal Size 2.5 2.00 (51) 1.31 (33.5)</p>	Maximum Current	26A	26A	26A	Terminal, blue Branch Terminal, beige	0.24 (6)	8WA1011-1NF01 8WA1011-1NF02	3.20 3.20	100 100
	Wire Range	#22-#12 AWG	#22-#12 AWG	Solid 0.25 mm ² -4 mm ² Finely Stranded 0.5 mm ² -2.5 mm ²	Accessories				
	Voltage Rating	600V	600V	500V	Neutral busbar 6 mm x 6 mm 1104 mm long, 135 A		8GF9324-2	18.20	10
	Wire Strip Length	0.43 (11)			Feeder terminal for neutral busbar Connection to:				
	Recommended Screw Tightening Torque	4.4 lb-in. (0.5 Nm)			4 mm ² AWG 10, 34A		8WA2860	.40	100
	Density	50 pcs/ft (166 pcs/m)			16 mm ² AWG 6, 82A		8WA2861	.65	100
 <p>Terminal Size 4 2.00 (51) 1.51 (38.5)</p>	Maximum Current	34A	40A	34A	Terminal, blue Branch Terminal, beige	0.26(6.5)	8WA1011-1NG31 8WA1011-1NG32	3.50 3.50	100 100
	Wire Range	#18-#10 AWG	#18-#10 AWG	Solid 0.5 mm ² -6 mm ² Finely Stranded 1.5 mm ² -4 mm ²	Accessories				
	Voltage Rating	300V	300V	500V	Neutral busbar 6 mm x 6 mm 1104 mm long, 135A		8GF9324-2	18.20	10
	Wire Strip Length	0.43 (11)			Feeder terminal for neutral busbar Connection to:				
	Recommended Screw Tightening Torque	4.4 lb-in. (0.5 Nm)			4 mm ² AWG 10, 34A		8WA2860	.40	100
	Density	46 pcs/ft (153 pcs/m)			16 mm ² AWG 6, 82A		8WA2861	.65	100
							35 mm ² AWG 2, 135A	2.50	25

Note: All dimensions shown in inches and (millimeters).

For reference purposes only. Not to be used for design or construction purposes.

For labeling accessories see pages 762-766. [Ⓞ]Not UL recognized.

13

Industrial Components

758



Type 8WA1 Neutral Isolating, Sliding Link Disconnect Terminals

Illustration	Approval	RU	SA	IEC	Description	Assembly Width	Catalog No	Price Each \$	Std Pack Qty	
Neutral Isolating Terminal for use in International Application, Provides for Mounting and Connection to 6 mm x 6 mm Neutral Bus Bar										
<p>Terminal Size 6</p>	Maximum Current	—	—	44 A	Terminal, blue	0.31	8WA1011-1NH01	3.60	100	
					Branch Terminal, beige	(8)	8WA1011-1NH02	3.60	100	
	Wire Range	Ⓞ	—	Solid 0.75 mm ² –10 mm ² Finely Stranded 1.5 mm ² –6 mm ²	Accessories					
	Voltage Rating	—	—	500V	Neutral busbar 6 mm x 6 mm 1104 mm long, 135 A		8GF9324-2	18.20	10	
	Wire Strip Length	0.43 (11)			Feeder terminal for neutral busbar					
	Recommended Screw Tightening Torque	7.0 lb-in. (0.8 Nm)			Connection to 16 mm ² AWG 10, 34A		8WA2861	.65	100	
Density	38 pcs/ft (125 pcs/m)			35 mm ² AWG 2, 135A		8JH4114	2.50	25		
				155 mm (6.1 in.) long		8WA1822-7AX00	3.60	10		
<p>Terminal Size 16</p>	Maximum Current	73A	—	82A	Terminal Blue	0.39	8WA1604	4.30	50	
					Branch Terminal, beige	(10)	8WA1011-1NK02	4.30	50	
	Wire Range	#12–#4 AWG	—	Solid 1.5 mm ² –16 mm ² Finely Stranded 4 mm ² –16 mm ²	Accessories					
	Voltage Rating	300V	—	500V	Neutral busbar 6 mm x 6 mm 1104 mm long, 135 A		8GF9324-2	18.20	10	
	Wire Strip Length	0.51 in. (13 mm)			Feeder terminal for neutral busbar					
	Recommended Screw Tightening Torque	10.62 lb-in. (1.2 Nm)			Connection to 16 mm ² AWG 10, 82A 35 mm ² AWG 2, 135A		8WA2861 8JH4114	.65 2.50	100 25	
Density	30 pcs/ft (100 pcs/m)									

Sliding Link Disconnect Terminal, Thermoplastic Body, with Screw Terminals on Both Sides and 2 Socket Holes for 4 mm Test Plug

Illustration	Maximum Current	RU	SA	IEC	Description	Assembly Width	Catalog No	Price Each \$	Std Pack Qty	
<p>Terminal Size 6</p>	Maximum Current	5A	44A	44A	Terminal (with recessed test socket)	0.31 (8)	8WA1011-1MH15	12.00	50	
					Terminal (without recessed test socket)	0.31 (8)	8WA1011-1MH11	9.60	50	
	Wire Range	#16–#10 AWG	#14–#8 AWG	Solid 0.75 mm ² –10 mm ² Finely Stranded 1.5 mm ² –6 mm ²	Accessories					
	Voltage Rating	600V [Ⓞ]	600V [Ⓞ]	500V [Ⓞ]	Barrier		8WA1822-7TH00	5.80	100	
	Wire Strip Length	0.43 (11)			Separator		8WA1825	.45	100	
	Recommended Screw Tightening Torque	4.4 lb-in. (0.5 Nm)			Links for 2 terminals, 44A		8WA1885	1.90	100	
	Density	38 pcs/ft (125 pcs/m)			Links for 3 terminals, 44A		8WA1886	2.60	100	
					Links for 10 terminals, 44A		8WA1888	6.10	100	
					Links for 10 terminals (unassembled)		8WA1822-7VH10	5.40	100	

Note: All dimensions shown in inches and (millimeters).
For reference purposes only. Not to be used for design or construction purposes.

For labeling accessories see pages 762-766.

ⓄRU pending.

ⓄAcross Isolating Gap:

RU, SA 330V

IEC 400V