







5SX Miniature Circuit Breakers

Selection

IEC/UL1077 Versions 5SX2

Description	Ordering Information
UL1077 maximum AC ratings One-Pole: 277V AC Two- and Three-Pole: 480V AC IEC maximum DC ratings 55V DC per pole	<ul style="list-style-type: none"> ▶ Select Circuit Breaker based on number of poles, rated current and desired trip curve characteristics see page 772. ▶ Accessories see page 771. ▶ Technical Data see pages 772-773. ▶ Dimensions see page 774.

5SX2 Miniature Circuit Breakers

Illustration	Description	Amp Rating	Standard C Curve Catalog No	High Inrush D Curve Catalog No	Semiconductors A Curve Catalog No	Residential B Curve Catalog No	Price \$
	One Pole	0.3	5SX2114-7	—	—	—	54.
		0.5	5SX2105-7	5SX2105-8	—	—	54.
		1	5SX2101-7	5SX2101-8	5SX2101-5	—	54.
		1.6	5SX2115-7	5SX2115-8	5SX2115-5	—	54.
		2	5SX2102-7	5SX2102-8	5SX2102-5	—	54.
		3	5SX2103-7	5SX2103-8	5SX2103-5	—	54.
		4	5SX2104-7	5SX2104-8	5SX2104-5	—	54.
		5	5SX2111-7	—	—	—	54.
		6	5SX2106-7	5SX2106-8	5SX2106-5	5SX2106-6	54.
		8	5SX2108-7	5SX2108-8	—	—	54.
		10	5SX2110-7	5SX2110-8	5SX2110-5	5SX2110-6	54.
		13	5SX2113-7	5SX2113-8	—	—	54.
		15	5SX2118-7	—	—	—	54.
		16	5SX2116-7	5SX2116-8	5SX2116-5	5SX2116-6	54.
		20	5SX2120-7	5SX2120-8	5SX2120-5	5SX2120-6	54.
		25	5SX2125-7	5SX2125-8	5SX2125-5	5SX2125-6	54.
		30	5SX2130-7	—	—	—	54.
32	5SX2132-7	5SX2132-8	5SX2132-5	5SX2132-6	54.		
40	5SX2140-7	5SX2140-8	5SX2140-5	5SX2140-6	54.		
50	5SX2150-7	5SX2150-8	—	—	54.		
63 [ⓐ]	5SX2163-7	—	—	—	54.		
	Two Pole	0.5	5SX2205-7	5SX2205-8	—	—	108.
		1	5SX2201-7	5SX2201-8	5SX2201-5	—	108.
		1.6	5SX2215-7	5SX2215-8	5SX2215-5	—	108.
		2	5SX2202-7	5SX2202-8	5SX2202-5	—	108.
		3	5SX2203-7	5SX2203-8	5SX2203-5	—	108.
		4	5SX2204-7	5SX2204-8	5SX2204-5	—	108.
		5	5SX2211-7	—	—	—	108.
		6	5SX2206-7	5SX2206-8	5SX2206-5	5SX2206-6	108.
		8	5SX2208-7	5SX2208-8	—	—	108.
		10	5SX2210-7	5SX2210-8	5SX2210-5	5SX2210-6	108.
		13	5SX2213-7	5SX2213-8	—	—	108.
		15	5SX2218-7	—	—	—	108.
		16	5SX2216-7	5SX2216-8	5SX2216-5	5SX2216-6	108.
		20	5SX2220-7	5SX2220-8	5SX2220-5	5SX2220-6	108.
		25	5SX2225-7	5SX2225-8	5SX2225-5	5SX2225-6	108.
		30	5SX2230-7	—	—	—	108.
		32	5SX2232-7	5SX2232-8	5SX2232-5	5SX2232-6	108.
40	5SX2240-7	5SX2240-8	5SX2240-5	5SX2240-6	108.		
50	5SX2250-7	5SX2250-8	—	—	108.		
63 [ⓐ]	5SX2263-7	—	—	—	108.		
	Three Pole	0.5	5SX2305-7	5SX2305-8	—	—	162.
		1	5SX2301-7	5SX2301-8	5SX2301-5	—	162.
		1.6	5SX2315-7	5SX2315-8	5SX2315-5	—	162.
		2	5SX2302-7	5SX2302-8	5SX2302-5	—	162.
		3	5SX2303-7	5SX2303-8	5SX2303-5	—	162.
		4	5SX2304-7	5SX2304-8	5SX2304-5	—	162.
		5	5SX2311-7	—	—	—	162.
		6	5SX2306-7	5SX2306-8	5SX2306-5	5SX2306-6	162.
		8	5SX2308-7	5SX2308-8	—	—	162.
		10	5SX2310-7	5SX2310-8	5SX2310-5	5SX2310-6	162.
		13	5SX2313-7	5SX2313-8	—	—	162.
		15	5SX2315-7	—	—	—	162.
		16	5SX2316-7	5SX2316-8	5SX2316-5	5SX2316-6	162.
		20	5SX2320-7	5SX2320-8	5SX2320-5	5SX2320-6	162.
		25	5SX2325-7	5SX2325-8	5SX2325-5	5SX2325-6	162.
		30	5SX2330-7	—	—	—	162.
		32	5SX2332-7	5SX2332-8	5SX2332-5	5SX2332-6	162.
40	5SX2340-7	5SX2340-8	5SX2340-5	5SX2340-6	162.		
50	5SX2350-7	5SX2350-8	—	—	162.		
	Three Pole plus Switched Neutral	10	5SX2610-7	—	—	—	216.
		16	5SX2616-7	—	—	—	216.
		20	5SX2620-7	—	—	—	216.
		25	5SX2625-7	—	—	—	216.
		32	5SX2632-7	—	—	—	216.
		50	5SX2650-7	—	—	—	216.

[ⓐ]Not UL recognized or VDE approved.