





Starters

 <p>25-40 Amp</p>  <p>50, 60 Amp</p>	Ordering Information <ul style="list-style-type: none"> ▶ Use complete catalog number. Replace the (*) with letter from the coil table. ▶ Select heater elements from appropriate table page 884. ▶ For additional information see Definite Purpose Catalog SFPC-18010. 	Coil Table <table border="1"> <thead> <tr> <th>60Hz</th> <th>50Hz Voltage</th> <th>Letter</th> </tr> </thead> <tbody> <tr> <td>24</td> <td>24</td> <td>J</td> </tr> <tr> <td>110-120</td> <td>110</td> <td>F</td> </tr> <tr> <td>200-208</td> <td>—</td> <td>D</td> </tr> <tr> <td>208-240</td> <td>190-220</td> <td>G</td> </tr> <tr> <td>277</td> <td>240</td> <td>L</td> </tr> <tr> <td>440-480</td> <td>380-440</td> <td>H</td> </tr> <tr> <td>550-600</td> <td>550</td> <td>E</td> </tr> </tbody> </table>	60Hz	50Hz Voltage	Letter	24	24	J	110-120	110	F	200-208	—	D	208-240	190-220	G	277	240	L	440-480	380-440	H	550-600	550	E
	60Hz	50Hz Voltage	Letter																							
24	24	J																								
110-120	110	F																								
200-208	—	D																								
208-240	190-220	G																								
277	240	L																								
440-480	380-440	H																								
550-600	550	E																								
<p>For other voltages and frequencies see Factory Modifications, page 458.</p>																										

6
Special Purpose Control

Class 16

FLA	Locked Rotor Amps			Poles	Normally Open Interlock	Open Type Starters with Ambient Compensated Bimetal Overload Relays ^①	
	240V	480V	600V			Catalog No	Price \$
25	150	125	100	2	—	16AF15A*8	128.
				2	1	16AF12A*8	136.
				3	—	16AF35A*4	139.
				3	1	16AF32A*4	159.
				4	—	16AF25A*4	164.
30	180	150	160	2	—	16BF15A*8	146.
				2	1	16BF12A*8	154.
				3	—	16BF35A*4	157.
				3	1	16BF32A*4	167.
				4	—	16BF25A*4	172.
40	240	200	160	2	—	16CF15A*8	162.
				2	1	16CF12A*8	169.
				3	—	16CF35A*4	172.
				3	1	16CF32A*4	182.
				4	—	16CF25A*4	187.
50	300	250	200	2	—	16DF15A*8	311.
				2	1	16DF12A*8	326.
				3	—	16DF35A*4	339.
				3	1	16DF32A*4	360.
60	360	300	240	2	—	16EF15A*8	339.
				2	1	16EF12A*8	360.
				3	—	16EF35A*4	347.
				3	1	16EF32A*4	367.
75	450	375	300	3	—	16FE35A*4	398.
				3	1	16FE32A*4	439.
90	540	450	360	3	—	16GE35A*4	542.
				3	1	16GE32A*4	583.
120	720	600	480	3	—	16HF35A*81	670.
				3	1	16HF32A*81	711.
150	900	750	600	3	—	16IF35A*81	1307.
				3	1	16IF32A*81	1348.

①Contact Sales office for ratings above 150A.